

**450 SPECIFICATIONS****Engine**

Engine Type	4-stroke
Displacement	455 cc
Carburetion	34mm CV Mikuni
Cooling	Liquid
Starting	Electric with recoil backup

**Drivetrain**

Final Drive	Shaft
Transmission	P/R/N/L/H
Drive System	Automatic PVT
EBS (Engine Braking System)	Accessory

**Suspension**

Front Suspension	MacPherson strut with 8.2"/20.8cm travel in/cm
Rear Suspension	Fully independent, progressive rate with anti-roll bar; 9.5"/24.1cm travel in/cm

**Brakes**

Front/Rear Brakes	Single-lever hydraulic disc w/ hydraulic rear foot brake
-------------------	--

**Tires/Wheels**

Front Tires	25x8-12
Rear Tires	25x11-10
Wheels	Steel

**Dimensions/Capacities**

Wheelbase	50.5/128.3 in/cm
Turning Radius (inside tire)	65/165.1 in/cm
Dry Weight	696/315.7 lbs/kg
Length/Width/Height	83x48x48 / 210.8x121.9x121.9 in/cm
Seat Height	33.8/85.7 in/cm
Fuel Capacity	4.25 / 16.1 U.S. gallons/L
Front-Rack Capacity*	90/40.8 lbs/kg
Rear-Rack Capacity*	180/81.6 lbs/kg
Hitch	Std / Receiver
Hitch Towing Capacity*	1225/555.7 lbs/kg
Hitch Tongue Weight*	120/54.4 lbs/kg
Ground Clearance	11/27.9 in/cm

**Instrumentation/Features**

Gauge Type	Digital
Speedometer/Odometer	Standard
Tachometer	Standard
Tripmeter	Standard
Hourmeter	Standard
High Beam Indicator	Standard
Gear Indicator	Standard
Fuel Gauge	Electric
Warning Lights	Hi Temp / Low Battery
Rear Work Lights	Accessory
DC Outlet	Standard
Winch Pre-Wire	Standard

**Colors**

Colors	Green/Black; Red/Black
--------	------------------------