

500 EFI SPECIFICATIONS**Engine**

Engine Type	4-stroke
Displacement	499 cc
Carburetion	39mm Throttle Body
Cooling	Liquid
Starting	Electric with recoil backup

Drivetrain

Final Drive	Shaft
Transmission	P/R/N/L/H
Drive System	Automatic PVT
EBS (Engine Braking System)	Standard- Accessory, Deluxe- Standard
ADC (Active Decent Control)	Standard- N/A, Deluxe- Standard

Suspension

Front Suspension	MacPherson strut with 8.2"/20.8cm travel in/cm
Rear Suspension	Fully independent, progressive rate with anti-roll bar; 9.5"/24.1cm travel in/cm

Brakes

Front/Rear Brakes	Single-lever hydraulic disc w/ hydraulic rear foot brake
-------------------	--

Tires/Wheels

Front Tires	26x8R12; PXT
Rear Tires	26x11R12; PXT
Wheels	Standard- Steel, Deluxe- Cast Aluminum

Dimensions/Capacities

Wheelbase	50.5/128.3 in/cm
Turning Radius (Inside tire)	65/165.1 in/cm
Dry Weight	Standard- 728, Deluxe- 773 lbs/kg
Length/Width/Height	83x48x48 / 210.8x121.9x121.9 in/cm
Seat Height	33.8/85.7 in/cm
Fuel Capacity	4.13 / 15.6 U.S. gallons/L
Front-Rack Capacity*	90/40.8 lbs/kg
Rear-Rack Capacity*	180/81.6 lbs/kg
Hitch	Std / Receiver
Hitch Towing Capacity*	1225/555.7 lbs/kg
Hitch Tongue Weight*	120/54.4 lbs/kg
Ground Clearance	11.3/28.6 in/cm

Instrumentation/Features

Gauge Type	Digital
Speedometer/Odometer	Standard
Tachometer	Standard
Tripmeter	Standard
Hourmeter	Standard
High Beam Indicator	Standard
Gear Indicator	Standard
Fuel Gauge	Electric
Warning Lights	Hi Temp / Low Battery
Rear Work Lights	Standard- Accessory, Deluxe- Standard
DC Outlet	Standard
Winch Pre-Wire	Standard

Colors

Standard	Green/Black; Black/Silver; Red/Black
Deluxe	Blue/Black; Black/Silver